

# XDX / XDZ

## Over Inflator

The XDX/XDZ models are specifically designed for the tyre fitting industry.

The desired over-pressure value can be set in the top display and the final pressure in the lower display.

The automatic process will inflate to the over-pressure setting, then deflate to the final pressure setting.

The XDZ is a high flow model and can be used for inflating large or multiple tyres.

Contact Airtec Corporation for further technical information.



### Product Features

- Pressure Hold Time
- Purge function for Nitrogen Inflation
- Emergency Stop Control
- Large Backlit LCD

### Technical Specifications

Construction	: Diecast aluminium wall/surface mount enclosure (IP66)
Dimension	: 269W x 285H x 106D mm
Power requirements	: 220V-240VAC (optional 12VDC or 100~120VAC)
Units of measurement	: psi / kPa / bar / kg/cm <sup>2</sup>
Operating range	: 5-145 psi, 35-1000 kPa, 0.3-10.0 bar, 0.4-10.2 kg/cm <sup>2</sup>
Reading precision	: 1 psi / 5 kPa / 0.1 bar / 0.1 kg/cm <sup>2</sup>
Accuracy	: Up to $\pm 0.5\%$ FS
Operating temperature	: 0°C to +60°C [32°F to 140°F] (without heater) : -20°C to +60°C [-4°F to 140°F] (with heater)

### Optional Accessories



93.2802  
4 way  
Manifold Kit



94.0600  
Air filter /  
Auto-drain / Regulator



97.5058  
Core  
Retracting Tool



45.5652  
Remote  
Emergency Stop

