

HIGH Pressure Digital Tyre Inflator



XHB

The XHB is capable of achieving a flow rate of more than 3,000 litres/min and is specifically designed for quick inflation of large (OTR) tyres to a maximum pressure of 12.5 bar.

When use with a 4-way manifold kit, it can inflate multiple tyres simultaneously.

Suitable for use with standard or large bore valves and core extraction tools.

1/2" High Flow Valve

High Speed Inflation

Able to Inflate Multiple Tyres

Improves Productivity

Rugged and Durable Diecast Aluminium Enclosure

Large Backlight LCD Display

Vandal Resistant Mechanical Switches

Nitrogen Compatible

International Approvals

Applications



Truck / Fleet

Mining Truck




The world's largest range of digital tyre inflation equipment

www.airtecasia.com

Options - Factory Fitted



Piezo Switches



Cabinet Heater



12V DC External Battery




Desktop Charging Unit

Accessories - Supplied Separately




Manifold Kit - 4 Way



Core Removal Tool



Air Filter / Auto-Drain
/ Regulator



3/8" Steel Wire Braided Hose

Technical Specifications

Construction

Diecast Aluminium Enclosure

Degree of Protection

IP66

Power Requirement

12V AC/DC

100-120V AC 50/60Hz

220-240V AC 50/60Hz

Units of Measurement

psi / kPa / bar / kg/cm²

LCD Types

1 - psi / kPa / bar

2 - psi / kg/cm² / kPa

Operating Range

5-181psi / 35-1250kPa / 0.3-12.5bar / 0.4-12.8kg/cm²

Accuracy + or -

0.3psi / 2kPa / 0.02bar / 0.02kg/cm²

Operating Temperature

Without heater

0°C to +60°C [32°F to 140°F]

With heater

-20°C to +60°C [-4°F to 140°F]

Note : Outlet hose is not supplied with unit

Refer to Airtec Corporation (Asia) Pte Ltd standard warranty terms and conditions.

Airtec Corporation (Asia) Pte Ltd reserves the right to change specifications, modify designs and discontinue items without obligation.

ATERFÖRSÄLJARE :

BOAB HJULDELAR AB
www.boabhjuldelar.se
Tel. 0530 - 133 33

