



OTR Sidewall Systems

Our OTR Sidewall Systems provide the same superior inflation technology used in the standard system but incorporated into an extra quick assembly housing for use in places where there is a high volume of sidewall injuries. It can be assembled in minutes by just one technician.

Features

- **Seperating into two parts, the inner frame is simply dropped into the tyre section and positioned with the heat pad over the repair area.** Taking the outside frame component, the guide bars are pushed into place and locked off with the pins. The system is then pressurised, brought up to operating temperature and the timer set for the cure to take place.

Plus all the benefits of a Monaflex tyre repair system - see page 10.



tyre range

OTRS SYSTEM

14.00-24 TO 29.5-29

MOTRS SYSTEM

27.00R49 TO 45/65R45



can repair

RADIAL AND BIAS TYRES

REGULAR, WIDE BASE, SUPER WIDE BASE,
FLOATATION, SKIDDER AND TERRA TYRES

SIDEWALL REPAIRS ONLY



components

OTRS SYSTEM

TRRS D-R - CONTROL PANEL

OTRS H - STEEL FRAMEWORK

OSX2215H - HEAT PAD (OUTSIDE TYRE)

OSX2815H - HEAT PAD (INSIDE TYRE)

OS2117A - AIRBAG (OUTSIDE TYRE)

OS2517A - AIRBAG (INSIDE TYRE)

MOTRS

TRRS D-R - CONTROL PANEL

OTRSM H - STEEL FRAMEWORK

OSX3019H - HEAT PAD (OUTSIDE TYRE)

OSX3719H - HEAT PAD (INSIDE TYRE)

OS2921A - AIRBAG (OUTSIDE TYRE)

OS3221A - AIRBAG (INSIDE TYRE)