

TOUCHLESS 3D WHEEL DIAGNOSIS

HIGH PRECISION BALANCING







8



FROM **CEMB** EXPERIENCE

ER100 EVO balancer is the result of CEMB consolidated experience in the manufacturing of high technology garage and industrial balancers since 1946. Development and cooperation with the most important car and tyre manufacturers guarantee to the professionals in the garage equipment field:

Reliability

- Easy and quick use
- Accuracy
- Completely configurable
- Reduced cycle time!

INNOVATIVE DESIGN ERGOFAST


- With ER100 EVO CEMB widens its range of products ERGOFAST, maintaining the concepts of ergonomics and practicality together with the original design
- WBA Wheel Best Access
 Wide space to work inside the rim
- Innovative touch screen
- Ergonomic tool positioning CLOSE AT HAND!



CORE OF TECHNOLOGY

- **3D Laser Scan** Extraordinary accuracy and speed in 3D acquisition of wheel sizes with exact positioning of adhesive weights
- OPB One Plane Balancing Correction of both static and dynamic unbalance on one plane at once and with only one weight
- AutoAdaptive Mode The new tolerance calculation system
- Automatic rotation of the wheel in weight position
- External Laser Scan Complete wheel diagnosis including tire conicity and wear analysis in three different areas
- Side Laser Line laser indicator on the upper part of the wheel to ease the application of clip-on weights in the exact position
- Direct Matching Visualization of the best possible matching to reduce eccentricity
- ALU-S Balancing mode Adhesive weights on the internal rim planes with specific counterweight position indicator (position repeater)
- Led light to illuminate the working space inside the rim
- **Tyre Set** The software indicates the best wheel positioning on the vehicle to get the best ride (conicity) and to minimize wheel vibrations (eccentricity)
- Pneumatic wheel locking CEMB PATENT
 Floor to floor time reduction / Extremely easy and quick to use / Very accurate wheel centering
- VDD Virtual Direct Drive Very quick and maintenance free measurement system CEMB PATENT





3D Jaser Scan

SCAN EXTREME MEASURING PRECISION AND FASTER WEIGHT APPLICATION

- Touchless wheel distance and diameter measuring system which, combined with the external radial laser for width measurement, detects with 3D precision the dimensions of any profile, even the most complex; no intervention of the operator.
- Advanced technology that speeds up the dimensions reading process without penalizing reliability and precision.
- Brighter laser pointer that grants an extreme accuracy during correction thanks to a clear indication
 of the application point for stick-on weights.
- Greatest robustness for a long lasting usage. No moving parts are exposed, risks of damages are reduced.
- Easy maintenance.



One Plane Balancing

• **OPB** (One Plane Balancing), eliminates both static and dynamic unbalance with a single counterweight, indicating the exact position to apply the weight inside the rim.

The balancer automatically detects if it is possible to correct both unbalances with only one weight and activates **OPB program**.

A real revolution in wheel balancing. **OPB** saves you time while maximizing your productivity.



😥 👩 AutoAdaptive Mode

AutoAdaptive THE NEW TOLERANCE CALCULATION SYSTEM


The innovative tolerance calculation system AutoAdaptive Mode is based on the evaluation of the residual imbalance limit value corresponding to an acceptable perceived vibration. For each wheel that is balanced, the software AutoAdaptive Mode detects weight and dimensions and calculates the tolerance value that will cancel any vibration perceived on the steering wheel. AutoAdaptive Mode grants the highest comfort when driving, and together with OPB program, saves balancing time.

STANDARD ACCESSORIES

In 1952 Cemb created the cone adapters for balancing machines and since then the company continued developing and producing high precision centering systems for any type of wheel. **Cemb does not recommend the use of non-original adapters on its balancing machines.**








Single phase power supply	115 / 230 V 50/60 Hz
Max. absorbed power	0,15 kW
Balancing speed	100 rpm
Measuring cycle for 15 kg (33 lb) wheel	4.7 s
Measurement uncertainty	0,5 g
Avarage noise	< 70 dB (A)
Rim width setting range	1.5" ÷ 20" / 40 ÷ 510 mm
Rim diameter setting range	10" ÷ 30" / 265 ÷ 765 mm
Min./Max. compressed air pressure	7 ÷ 10 kg/cm ²
	~ 0.7 ÷ 1 MPa
	~ 7 ÷ 10 bar
	~ 105 ÷ 145 psi
Max. wheel weight	< 75 kg

Max.	wheel weight
Mach	nine weight







For more information see the complete brochure on the web site www.cemb.com

Wheel loading and removal without effort or adjustment

PERFECT CENTERING Wheel automatic lifting Ideal centering and more accurate balancing

220 kg

QUICK

Quicker than any other traditional lift A single pedal controls the whole working cycle

AUTOMATIC

Electronic system with PLC

UNIVERSAL

Applicable to any CEMB balancing machine



CEMB S.p.A. Via Risorgimento, 9 23826 Mandello del Lario (LC) - Italy www.cemb.com



\odot

Garage equipment division CEMB - ITALY Plant and Training Center Phone +39 0341 706111 garage@cemb.com

CEMB[®] USA - BL Systems Inc. 2873 Ramsey Road Gainesville, GA 30501 - USA Phone +1 678 717 1050 sales@cemb-usa.com www.cemb-usa.com



All the data and features mentioned in this catalogue are purely for information and do not constitute any commitment on the part of our company, which reserves the right to make any and all alterations it may consider suitable without notice.